

H480C



TECHNICAL DATA

DIMENSIONS [mm]

Width, head open	1880
Width, head closed	1200
Height without rotator and link	1450

WEIGHT [kg]

Without rotator and link, from	1350
--------------------------------------	------

FELLING/CUTTING

SuperCut 100 saw unit, automatic chain tensioning	Standard
Maximum cut diameter [mm]	710
Length of saw bar [mm]	825/900
Chain type404
Chain speed [m/s]	40

FEEDING, FOUR-WHEEL-DRIVE with steel feed rollers

Gross feed force [kN]	400 / 630-cc: 27
	500 / 800-cc: 30
	500 / 780-cc: 30
Maximum feed speed [m/s]	4.0–6.5
Maximum roller opening [mm]	680

DELIMBING [mm]

Delimiting knives	4 moving, 2 fixed
Delimiting diameter tip to tip	460
Maximum opening upper knives	680
Maximum opening lower knives	710

HYDRAULIC SYSTEM

Maximum operating pressure [MPa]	28
Recommended pump capacity [l/min.]	260–340

CONTROL AND MEASURING SYSTEM For adaptation, contact your local Waratah dealer.

OPTIONAL EQUIPMENT

Color marking	Yes
Stump treatment	Yes
Multi-tree-handling (MTH)	Yes
MenSe feed rollers	Yes
Moipu feed rollers	Yes
Steel thumbnail feed rollers	Yes
Steel V-profile feed rollers	Yes
Steel ribbed feed rollers	No
Chain and saw bar kits	Yes
Hydraulic hose kit	Yes
Top saw	No

OTHER ACCESSORIES For more information, please contact your dealer.